



T5 VAPOR PROOF LIGHT

- KOJIN Vapor Proof light is IP65 rated
- Designed for damp or wet locations, indoors and outdoors
- Comes with a clear impact resistant acrylic ribbed cover that can withstand most harsh environments
- Great for parking garages, car washes, kitchens and covered walkways
- Compatible with motion and occupancy sensors
- Available in 2-lamp, standard or high-output, universal voltage 120-277V or 347V
- UL and cUL Classified, a testament to our ongoing commitment to safety
- Reduce energy consumption without compromising lighting quality
- Qualifies for government / utility rebates (where available)
- 3 Year Warranty
- Made in Taiwan





T5 VAPOR PROOF LIGHT

Specifications

Dimensions

KT5VP120-L2 = 48.8" (124 cm) X 4.72" (12cm) X 3.94" (10cm)

Weight

KT5VP120-L2 = 4.85lbs (2.2kg)

Electrical Specifications

Power Factor: ≥ 0.99

Input Power

KT5VP120-L2 = 2 X 28W

Ballast Factor @ 120V

KT5VP120-L2 = 0.93

Ballast Factor @277V

KT5VP120-L2 = 0.93

Total Harmonic Distortion $\leq 7.5\%$

Operation Frequency: 50-60HZ

IP Rating: IP65

Preheat Time: 1-2 seconds

Energy Efficiency Index: $\geq 90\%$

Internal Protection Functions: Protection Circuit

Ambient Temperature: $-10^{\circ}\text{C} - +55^{\circ}\text{C}$

Storage Temperature: $-20^{\circ}\text{C} - +55^{\circ}\text{C}$

Relative Humidity: $\leq 80\%$

Ballast Type: Electronic

Starting Method: Instant Start

Input Voltage: AC 120V-277V, 347V

Lamp Connection: Parallel, Series

Input Frequency: 50/60 Hz

Ballast Life: 50,000 hours

Warranty:

Guaranteed for one (1) year against mechanical defects in manufacture. Factory installed internal components such as ballast and wiring are guaranteed for three (3) years from date of purchase. Warranty applies to repair or replacement of defective parts and does not include labor costs.

Approvals:

UL and cUL Classified

How To Order

Series	Length	Lamps	Voltage
KT5VP	4' = 120	2 Lamps = L2	120-277V = UV

02/2016

